

EXTERNAL ADJUST SNUBBER

AMKO



Dimensions = 32mm a/f hex, 67mm long overall.

FEATURES

- Hydrostatically tested to 1.5 times max working pressure.
- Can be supplied to NACE MR-01-75-Latest edition.
- Has trace code on body with original mill certificates available for all wetted parts on request.
- Materials ;316 STST-monel-brass etc.
- Gauge snubber is adjustable restriction type and helps protect instrument against pulsing and surges in process system. Suitable for use with pressure gauges, pressure switches and pressure transmitters etc.
- Maximum working pressure 420 bar (6000 psi)

HOW TO ORDER

PART No IL-GS- M or F- M or F-

Standard Rating = 6000psi
add HP at end of Part No
for 10000psi rating

↑
Inlet

↑
Outlet

↑
Material

Inlet and Outlet Codes			Material Codes
Select M or F for Male or Female			
03 = 1/4" NPT	04 = 1/4" BSPP	13 = 1/4" BSPTaper	AI = AISI 316 S/S
05 = 3/8" NPT	06 = 3/8" BSPP	14 = 3/8" BSPTaper	MO = MONEL
07 = 1/2" NPT	08 = 1/2" BSPP	15 = 1/2" BSPTaper	BR = BRASS
09 = 3/4" NPT	10 = 3/4" BSPP	16 = 3/4" BSPTaper	
11 = 1" NPT	12 = 1" BSPP	17 = 1" BSPTaper	Add AL at end of Part No when NACE MR-01-75 is required